

P340

Smart 12MP Ultra HD PoE Bullet Camera with Person/ Vehicle Detection and Two- Way Audio

- Person/Vehicle Detection
- 12MP Ultra HD
- Color Night Vision

Specifications

Video & Audio	
Image Sensor	1/2.49" CMOS Sensor
Video Resolution	4512×2512 (12 Megapixels) at 20 fps
Lens	f=4.0mm; F=1.6, with IR-cut filter
Video Format	H.265
Field of View	Horizontal: 93°; Vertical: 49°
Day & Night	Auto-switching with IR-cut filter
Infrared Night Vision	30 meters (100ft) (LED: 2pcs/28mil/850nm)
Color Night Vision	Spotlight: 1pc/4.3W/6500K/700 Lumens
Audio	Two-way audio
Power	
PoE	IEEE 802.3af, 48V Active
DC Power	DC 12.0V 1A, <12W
Interface	

Power	DC power port
System	Reset button
Ethernet	One 10M/100Mbps; RJ45
Storage	Micro SD card slot (Max. 256GB)
Audio	Built-in microphone and speaker
Software Features	
Frame Rate	Mainstream: 2fps - 20fps (default: 20fps); Substream: 4fps - 20fps (default: 10fps)
Code Rate	Mainstream: 3072Kbps - 10240Kbps (default: 8192Kbps); Substream: 128Kbps - 1024Kbps (default: 768Kbps)
Browsers Supported	Edge, Chrome, Firefox, Safari
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Smart Alarm	Motion detection/person detection/vehicle detection/ pet detection
Record Mode	Motion-triggered recording (default); scheduled recording; 24/7 recording
Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Maximal User Access	20 Users (1 admin account & 19 user accounts); support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
Work with	Google Assistant
Working Environment	
Temperature	Operating temperature: -10°C~+55°C (14°F~131°F)
Humidity	Operating humidity: 10% ~ 90%
Weatherproof	IP67
Size & Weight	
Dimension	Φ67*187mm
Weight	460g
Warranty	
Limited Warranty	

2-year limited warranty. For support, visit <https://support.reolink.com/hc/en-us/>

www.reolink.com