

RLN12W

12-Channel Wi-Fi 6 NVR recorder with 2TB built-in HDD for 24/7 local video recording

- 12-Channel Wi-Fi 6 NVR
- Dual-Band Wi-Fi Connection
- 2TB HDD Pre-installed




Specifications

Video/Audio Input	
IP Video Input	Up to 16 IP Cameras
Audio Input	Cameras with built-in mic
Video/Audio Output	
Video Output	VGA, HDMI
Display Resolution	HDMI: 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768 VGA: 1920x1080, 1280x1024, 1280x720, 1024x768
Audio Output	1-channel, RCA
Decoding	
Video Compression	H.265/H.264


Live View / Playback Resolution	7680×2160, 4608×1728, 4512×2512, 4096×3072, 3840×2160, 2560×2560, 2560×1920, 2560×1440, 2048×1536, 2304×1296, 1080p, 720p
Synchronous Playback	Up to 4 channels
HDD	
SATA	1 x SATA interface (1 x 2TB HDD included)
Capacity	Up to 16TB
External Interface	
USB Interface	2 x USB 2.0
Network Interface	4 x RJ-45, 10/100 Mbps self-adaptive (for IP cameras) 1 x RJ-45, 10/100 Mbps self-adaptive (for LAN/WAN)
Wi-Fi	
Wireless Standard	IEEE 802.11a/ac/ax/ b/g/n
Operating Frequency	2.4 GHz/5 GHz
Wireless Security	WPA/WPA2/WPA3
Network	
Network Protocols	HTTPS, TCP/IP, UDP, DHCP, P2P, UPNP, RTMP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP
Browser Supported	Edge, Firefox, Chrome, Safari
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Max. User Access	Max. 20 users (1 admin & 19 user); Max. 12 simultaneous streams (10 sub & 2 mainstreams)
General	
Power Supply	DC 12V/2A
Power Consumption	<10W (with 2TB HDD)

Working Environment	Temperature: -10°C ~ +45°C (14°F ~ 113°F); Humidity: 10% ~ 90%
Dimensions	255mm(W) x 49.5mm(H) x 222.7mm(D)
Weight	1.4kg
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

Gallery & Specs



1. Power LED
2. HDD LED
3. USB Port



1. Antenna
2. Reset Button
3. Power Input
4. USB Port
5. HDMI Port
6. VGA Port
7. Audio Output
8. LAN Port (For Internet)
9. LAN Port (For IP camera)